

FT902 FT PONORNÝ CHLADIČ**FT902 FT immersion cooler**

Ponorné chladiče JULABO sa používajú predovšetkým na chladenie pri napojení na vykurovacie obehotové čerpadlo alebo na rýchle ochladzovanie kvapalín až na nízke teploty.

JULABO immersion coolers are primarily used for counter-cooling when connected to a heating circulator, or for rapidly cooling fluids down to low temperatures.



Parametre	Parameters
<ul style="list-style-type: none"> Chladenie ponornou sondou. Chladenie kvapalín až na nízke teploty. Protichladenie otvorených cirkulačných kvapalín na teplotu okolia alebo nižšie. Integrovaná regulácia teploty a externý snímač Pt100. Rozsah pracovných teplôt od -90 °C do 30 °C. Teplotná stabilita ±1. Teplota okolia od 5 °C do 35 °C 	<ul style="list-style-type: none"> Cooling with a submersible probe. Cooling liquids down to low temperatures. Anti-cooling of open circulating fluids to ambient temperature or below. Integrated temperature control and external Pt100 sensor. Working temperature range from -90 °C to 30 °C. Temperature stability ±1. Ambient temperature from 5 °C to 35 °C
Laboratórium (miestnosť)	Laboratory (room)
Laboratórium pre meranie výmenníkov tepla (VC 1.16)	Laboratory for measuring heat exchangers (VC 1.16)
Zodpovedná osoba	Responsible person
Ing. Peter Hrabovský, PhD.	